

# SHORT THROW SERIES IN114BBST



## XGA - 3500 ☀️ - 4:3 Aspect Ratio

The IN114BBST short-throw projector does more with ultra-long lamp life, high brightness, and amazing connectivity. Beam more perfect images and engage your audience with 2 HDMI inputs, VGA, video, and audio capability. Plus, the compact design and lightweight makes it as easy to move around as it is to install.

## Features

### Low Latency Gaming Mode

Improved communication time from the input source to your projector allows for an enhanced gaming experience.

### USB-A Power for Devices

Power your external devices like Amazon Firestick or Roku with the convenient USB-A input right on the projector.

### Industry-leading Lamp Life

The Genesis Series features up to an unprecedented 15,000 hours of lamp life when used in Dynamic Mode. With no filters to replace, these projectors are an unbeatable value.

### High Brightness

Get better, brighter images on any surface, in any light. The Genesis Series has up to 3800 lumens.

### Advanced Digital Image Correction

With the new digital edge masking and image shift features – we make getting those final image adjustments perfect.

### Zoom

The zoom ratio adds flexibility for installations using pre-existing mounts. Adjust the zoom to create the perfect image in the same space.

## Image

Projection Technology	Texas Instruments DLP®
Panel Size	0.55" DMD
Native Resolution	XGA
Pixels	1024 x 768
Aspect Ratio	4:3
Contrast Ratio	30000:1
Brightness (Lumens)	3500
Light Source	UHP Lamp / SP-LAMP-105
Light Source Life Maximum Hours	15000
Maximum Supported Resolution	1920 x 1200
Horizontal Sync. Range (KHz)	31.469 ~ 97.551
Vertical Sync. Range (Hz)	56 ~ 85

Uniformity (%) 80

## Optical

Lens -  
Lens Zoom Adjustment Manual  
Optional Lenses -  
Image Offset (%) 115  
Focal Length (mm) 7.15  
F-Stop 2.7  
Vertical Lens shift (%) 5%  
Horizontal Lens shift (%) 5%  
Keystone Adjustment Manual  
Vertical Keystone Correction  $\pm 20$   
Horizontal Keystone Correction -  
Projection Factor 0.621:1  
Projection Distance (Meters/Feet) 0.4 ~ 3.76 / 1.3 ~ 12.3  
Optical Zoom 1:1  
Digital Zoom Demagnification / Magnification 0.8x ~ 2.0x  
Focus Adjustment Manual

## Connectivity

Analog Input VGA, S-VIDEO  
Analog Output VGA  
Digital Input HDMI™ 1.4 x2  
Digital Output -  
Audio Input 3.5mm  
Audio Output 3.5mm  
Control RS232, IR Remote, KeyPad  
Service USB-A  
Powered USB for Wireless Dongle USB-A  
3D Sync Yes  
Full 3D Support Yes  
3D Formats All Major Formats Supported  
Document Reader -  
Video Player -  
Photo Viewer -  
Music Player -  
PC Less Compatibility -

## Power

Power Supply 100-240 V AC; 50 ~ 60 Hz  
Power Consumption Max (W) 267  
Power Consumption Min. (W) 210  
Power Consumption Network Standby (W) -  
Power Consumption Standby (W) <0.5

## General

Dimensions (W x H x D) (mm / in)	236 x 313 x 107 / 9 x 12 x 4
Product Weight (Kilograms/Pounds)	2.6 / 5.7
Fan Noise (dB)	30
Audio (W)	10
Operating Temperature (Celsius/Fahrenheit)	5 ~ 40 / 41 ~ 104
Operating Humidity (%)	-
Max Operating Altitude (meters / feet)	3048 / 1000
Storage Temperature (Celsius/Fahrenheit)	-
Storage Humidity (%)	-
Security	Kensington Security Slot™, PIN Code Lock & Timer
In the Box	Power cord, VGA cable, Safety instructions, User documentation, Remote control without batteries
Safety and Regulatory	-
Environmental	-