



## PenlouchPT - 75"





( 1800 572 5949

## PRODUCT SPECIFICATION

Model Name	PenTouch PT 75"	ТОИСН	
ACTIVE SCREEN SIZE ("INCH)	75"	TOUCH SURFACE MATERIAL	TOUGHENED TEMPERED GLASS
DISPLAY BACKLIGHT	LED	TOUCH SURFACE TECHNOLOGY	ANTI-GLARE GLASS (NEW GENERATION GLASS OPTIONAL)
DISPLAY AREA	1652*930MM	PROTECTION	3M ANTIGLARE
DISPLAY RATIO	16 : 9	TRANSPARENCY	>88%
RESOLUTION	3840*2160	HAZE	2%-5%
DISPLAY COLORS	8 BIT + FRC (1.07 BILLION)	TOUCH SURFACE HARDNESS	н7
CD BRIGHTNESS	450CD/M2	TOUCH SENSOR	INFRARED TOUCH
CONTRAST RATIO (TYPICAL)	4000:1	TOUCH POINTS	20 POINTS UNDER WINDOWS   10 POINTS UNDER ANDROID
RESPONSE TIME (TYPICAL)	4MS	TOUCH SCREEN WRITING TOOLS	NANO PEN (>3MM WIDTH) INCLUDED OR FINGER
/IEWING ANGLE	178°	TOUCH RESPONSE TIME	≤10MS
JFE TIME (WORKING HOURS/DAY)	>50,000 HOURS	POSITIONING ACCURACY	±2MM
OWER CONSUMPTION	MAXIMUM ≤400W STANDBY MODE ≤0.5W	TRANSMISSION RANGE	SM
NORKING VOLTAGE	AC 100-240V, 50/60HZ	COMMUNICATION INTERFACE	USB
DISPLAY ORIENTATION	LANDSCAPE		
		TRANSPORTATION / STORAGE	
AV PORTS		STORAGE TEMPERATURE/HUMIDITY	-15°C~55°C/20~90%RH(NON COAGULATION)
RONT INTERFACE INPUTS	HDMI 1.4 X 1, USB(TOUCH) X 1, USB(PUBLIC) X 2, MICX1	WORKING TEMPERATURE/HUMIDITY	0°C-40°C/20~80%RH(NON COAGULATION)
REAR AV INPUTS	HDMI 2.0(4K@60HZ*2) X 2, DP1.2(4K@60HZ) X 1, VGA(1920X1080@60HZ)X1&PC AUDIOX1, USB(TOUCH) X 4	INSTALLATION METHOD (OPTIONAL)	WALL-MOUNTED / FLOOR STAND
		OUTLINE DIMENSION (WITHOUT WALL MOUNT BRACKET THICKNESS)	1770*1071*109MM
AV OUTPUTS	HDMI OUT (SUPPORT 4K@60HZ, 1920X1080@60HZ)X 1	PACKING DIMENSION	1894X1193X247MM
	USB2.0(PUBLIC) X 1,USB3.0(PUBLIC) X 1, USB 2.0	NET WEIGHT	APPROX.56KG
OTHER	EMBEDDED X 1, R5232 X 1, RJ45 X 2, OPS SLOTS (4K@60HZ) X 1, DC 5V-2A OUT, LINE OUT X1, SPDIF OUT X1	GROSS WEIGHT	71±2KG
MULTIMEDIA FILE FORMATS SUPPORT	IMAGE: JPEG, BMP, PNG	VESA MOUNT INSTALLATION POSITION	800X400MM
	VIDED: MPE01, MPE62, MPE64, SORENSONH.263, H.263, H.264, HEVC/H.265, MVC, AVS, AVS+, WMV3, VC1, MOTION JPEG, VPB, VP9, RV30/KV40 AUDIO: MPEG1/2 @LAYER1;@LAYER2;@LAYER3, EAC3, ACC-LC, HEAAC, VORBIS, LPCM, IMA-ADPCM, MS-ADPCM, G711 A/MU-LAW, LBR(COOK), FLAC	000 00	
		OPS PC	
		MODEL	S044P621
		CPU	INTEL 15-7200U
INTEGRATED SOFTWARE FOR IMPORTING FILES FROM MS-WORD, PPT AND PDF	YES POSSIBLE BY OUR SPECIAL SOFTWARE - TEACH INFINITY II	RAM	BGB DDR4
		HD DRIVE	1286 SSD
CROP DATE FROM YOUTUBE, LECTURE WEBINARS	YES POSSIBLE BY OUR SPECIAL SOFTWARE - TEACH INFINITY II	MIC	3.5MM*1
		HDMI	1; HDMI 1.4 4K@24HZ
INSERT IMAGE, VIDEO AND CAMERA CAPTURE AND SAVE SESSION AS PPT, PDF, JPG & MS-WORD	YES POSSIBLE BY OUR SPECIAL SOFTWARE - TEACH INFINITY II	LINE OUT	3.5MM*1
5255104 A5 FF1, F07, 5F0 & M5 HORD		USB 2.0	2
INTERACTIVE PANEL SHOULD HAVE SOFTWARE TO WIRELESSLY CONNECT ANY DEVICE - WIN 7/8/10, ANDROID & IOS	YES POSSIBLE BY OUR SPECIAL SOFTWARE For Casting	USB 3.0	2
		1000 MBIT/ RJ45	1
3 YEARS COMPREHENSIVE ONSITE WARRANTY WITH PHYSICAL DAMADE FROM OEM REQUIRED	YES	BUILD-IN WIFI	1
		OPS INTERFACE	TX24A SUPPORT 4K#60HZ
		os	PRE-INSTALL WIN 10 PRO ENGLISH (NON-LICENSE)
	SDE	AKERS	
SPEAKER POSITION	FORWARD	SPEAKER FREQ. RESPONSE	180HZ - 20KHZ
SPEAKER RATED IMPEDANCE	80	SPEAKER MAX.POWER OUTPUT	15W*2
	AND	ROID	
HIPSET	МТК8386	GUI - GRAPHIC USER INTERFACE	
PU	ARMVB A73*2+A53*2 (A53 : 1.05-1.3GHZ; A73 : 1.15-1.5GHZ)	DISCUSSION / WHITE BOARD	
PU	MALI-G51MP2 650MHZ	CUSTOMIZED GUI	
IAM	308	MULTIMEDIA FILE FORMATS SUPPORTED	
юм	32 GB ROM Built-IN	OBJECT RECOGNITION	
XTERNAL MEMORY	32GB TF CARD (BUILD IN)	BLUE LIGHT FILTER	
INDROID VERSION	8.0.0	OPS PC	
INDROID RESOLUTION	4K		
NTELLIGENT THERMAL PROTECTOR	AUTOMATIC HIBERNATE WHEN OVER HEATED		

BUILT - IN APPS Everything you need to schedule meetings, manage e-mails, save and open files with the cloud and work on documents, all with PenTouch buit-in apps. Collaborate locally and remotely, easily

## PENTAGON TECH FUSION SERVICES PVT LTD

A80, Ground Floor, DDA Sheds, Okhla Industrial Area, Phase 2, New Delhi- 110020



**(** 1800 572 5949