



**Pentagon**  
Tech Fusion Services Pvt. Ltd.



**GeM**  
Government  
e Marketplace

## PenTouch PTLV 110



### FEATURES

- Perfect 4K resolution
- Front audio stereophonic speaker
- Industrial grade aluminum frame
- Multiple signal input HDMI, VGA, Video, YPbPr, TV etc.
- Infrared touch technology for rich writing experience
- Password / Pattern Lock protected
- 4mm protect glass and anti-scratch
- 20 points touch, in-built Screen recorder, 4ms response time
- Support APK install & authorize management, permit or forbidden application

**android 11**

### Technical Specification

#### LCD Panel

Diagonal Size	110"
Backlight Type	D LED
Aspect Ratio	16:9
Response	4ms
Resolution	3840 x 2160
Contrast Ratio	15000:1
Brightness(cd/m <sup>2</sup> )	500cd/m <sup>2</sup>
Display area	1209mm(H) X 680mm(V)
Color	1.07 billion Colors (10 BIT)
View Angle	178°

#### System

OS	Android 11.0 Amlogic T982, Quad Core Cortex-A55, 1.5GHz
GPU	Mali - G52
RAM	4 GB/8 GB
FLASH (Memory)	Flash (Memory) 32 GB/64 GB/128 GB

#### I/O Port

Rear Input	HDMI IN*2, USB2.0*1, USB3.0*1, TOUCH USB*1, RS-232*1, Earphone*1, COAX*1, RS-232*1, 2.4G Wi-Fi*1, 5G WiFi*1, 5G Hotpoint*1, Bluetooth5.0*1, AV input*1, VGA IN*1(optional), PC-AUDIO*1(optional), YPbPr Input*1(option), HDMI Output (option), RF Tuner (option)
------------	--



Front Input Type-C\*1, (Default is the features of USB and Charge; The features of HDMI Input, LAN, USB are Options), USB\*3, HDMI\*1, Touch USB \*1

### Media Format

Audio Mp3, WMA, WAV, APE, FLAC, AAC, OGG, M4A, 3GPP

Video H.264, VP 8, RV, WMV, AVS, H.263, MPEG4

Picture JPG, BMP, PNG

### Touch Features

Touch Type Infrared Touch, 20points Touch

Glass 4mm, Morse 8 grade tempered glass, Explosion proof, anti glare, etc.

Transmittance >92%

Response Time 4ms

Touch Precision ≤1mm

Touch Object All Opaque object, such as finger, pen etc

MTF 60 million touch by each points

Minimum Touch Object ≥1mm

Anti light Incandescent lamp (220V,100W) Distance > 350mm, Sunlight illumination<90000Lux

Interface USB

### Audio

Speaker 2 x 20W (Stereo)

### OPS PC (optional)

CPU Core i3 / Core i5 / Core i7

Memory Option 4GB / 8GB / 16GB / 32GB

Hard disk SSD: 128GB/256GB + Option to connect SATA HDD upto 4 TB

I/O port USB2.0\*2, USB3.0\*2, MIC\*1, LINE OUT\*1, RJ45\*1, VGA\*1, HDMI\*1

OPS Dimension 30mm or 42mm

### Tech Features

Language English

Video Format PAL, NTSC

Working Mode 24x7 hrs

Display Light 60,000\* hrs

Frequency Horizontal Frequency : 20 ~ 82KHz (Anolog & Digital) Vertical Frequency: 55 ~ 75Hz

Optimum Resolution 3840 x 2160 @ 60HZ

Support Resolution 3840 x 2160, 1920 x 1080, 1680 x 1050, 1600 x 1200, 1440 x 1050, 1360 x 768, 1280 x 1024  
1280 x 768, 1024 x 768, 832 x 624, 800 x 600, 720 x 400, 600 x 480

Video Format 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 4K

### Function Features

Amazing OSD Humanity beautiful OSD, Touch control

Multiple Control Support remote control, keyboard, RS232, Touch control

Touch OSD Touch slide from bottom to start the hidden OSD menu

Sunlight Readable Suit for lots of place, it can readable at sunlight

Touch 20 points touch

Multiple I/O Support HDMI / VGA / CVBS / YPbPr / Display Port / TV

Input Auto Scan Auto scan the input signal, and countdown tips

Customize Mode Preset Standard, Warm, Cinema, Meeting work mode and support customize

Airplay iPhone, iPad wireless display on TAIO monitor by airplay

Software White board, Mirror display, Comment etc.



## Physical Features

Power Supply	AC 100 ~ 240V/ 2-5A, 50-60Hz,
Consumption	Working $\leq$ 200W, Standby $\leq$ 0.5W
Body material	Aluminium, Metal
Color	Deep Grey Front, Black Cover
Temperature	Work: 0°C ~50°C, Storage: - 10° ~ 60°C
Humidity	Work: 10% to 90%, Storage: 0 to 95% (Non-Condensing)
Noise	Working Noise<50dBA
Product Dimension	1479.9*923.6*106.1mm
VESA hole	400 x 200 mm (4*M8 screw)
Weight	NW: 38Kg $\pm$ 1.5Kg, GW: 47Kg $\pm$ 1.5Kg
Package Dimension	1600*1025*215MM
<b>Other</b>	
Accessories	Remote control*1, Power Cord*1, Wi-Fi antenna *1, USB TOUCH CABLE
Option	HDMI, DVI, VGA, BNC, Wall Mount Bracket / Floor stand set
Certificates	BIS, CE, RoHS, GMP, ISO 9000:1, ISO 2700:1

## PENTAGONTECH FUSION SERVICE SPVT LTD

A-80, 3<sup>rd</sup> Floor, DDAC Commercial Complex, Okhla Industrial Area, Phase 2  
New Delhi - 110020

+91 - 11 - 46561005

+91 - 9599599041 / 42

+91 - 8076924850



info@pentagontech.in



1800 572 5949



www.pentagontech.in



# Pentagon